The VIPER LSU 135 is a wet/dry professional vacuum cleaner. It is easy to use, robust and has optimal suction power.

LSU product family has a modular design with different tank capacities and motor quantities. Tank capacity for LSU 135 is 35 litres and it has one motor. You can choose stainless steel tank or red plastic tank. As standard, the machine is delivered with the following accessories: crevice tool, round dusting brush, wet pick-up tool and dry pick-up tool.

- Easy to use and service
- Optimal suction power •
- Robust chassis
- Cable storage
- For wet or dry vacuum applications



Picture shown may not represent model quoted

	Included accessories	Ref. no.	Min. required	LSU135-EU	LSU135-UK	LSU135P-UK	
Nozzle							
X	DRY PICK-UP TOOL	VA80036	1	•	•	•	
Vac Nozzle W	Vet						
×	PICK-UP TOOL	VA80853	1	•	•	•	
Round Brush Nozzle							
	DUSTING Ø 38 MM	VA20803	1	•	•	•	
Crevice Nozz	le				1		
	CREVICE TOOL Ø 38 MM	VA20806	1	•	•	•	
Filter							
8	35L ABSORBING DUST FILTER	VA80706	1	•	•	•	
Tube							



### • Standard equipment

Non TUBE ASSEMBLYVA804011MAND ASSEMBLYVA807111ModelLSU135-EULSU135-EULSU135-EULSU135-EULSU135-EURef. no.50001105000112500011350001135000113RCDUCT FURES15000113500011350001135000113To out rest11To out rest1To out restYoung modelYYoung modelYoung modelYoung modelYoung modelYoung model <th colspan="2">Included accessories Ref. no</th> <th>Ref. no.</th> <th>Min. required</th> <th>LSU135-EU</th> <th>LSU135-UK</th> <th>LSU135P-UK</th>	Included accessories Ref. no		Ref. no.	Min. required	LSU135-EU	LSU135-UK	LSU135P-UK
AndelLSU135-EULSU135-UKLSU135P-UKModelS00001105000011250000113Ref. no.500001105000011250000113PRODUCT FEATURES•••Tip out recovery tank•••Easy-to-carry handle•••Technical specificationsLSU135-EULSU135-UKLSU135P-UKVacuum motor type2-stage2-stage2-stageVoltage (V)220-240220-240220-240Protection classX4X4X4Rated power (W)100010001000Max. airflow (m²/h - I/min.)150/2500150/2500150/2500Vacuum (mm H2O)202020202020Sound pressure level (dB(A))747474Cable length (m)7/orange7/orange7/orangeTank capacity (I)353535Length x width x height (cm)47x45x8047x45x8047x45x80	$\bigcirc$	SUCTION TUBE ASSEMBLY	VA80401	1	•	•	•
Ref. no.     5000110     5000112     5000113       PRODUCT FEATURES     .	7	WAND ASSEMBLY	VA80711	1	•	•	•
PRODUCT FEATURES       Tip out recovery tank     •     •     •       Easy-to-carry handle     •     •     •       Technical specifications     LSU135-EU     LSU135-UK     LSU135P-UK       Vacuum motor type     2-stage     2-stage     2-stage       Voltage (V)     220-240     220-240     220-240       Prequency (Hz)     50-60     50-60     50-60       Protection class     X4     X4     X4       Rated power (W)     1000     1000     1000       Max. airflow (m*/h - I/min.)     150/2500     150/2500     150/2500       Sound pressure level (dB(A))     74     74     74       Cable length (m)     7/orange     7/orange     7/orange       Tank capacity (I)     35     35     35	Model			LSU135-EU	LSU1	35-UK	LSU135P-UK
Tip out recovery tank     •     •     •       Easy-to-carry handle     •     •     •     •       Technical specifications     LSU135-EU     LSU135-UK     LSU135P-UK       Vacuum motor type     2-stage     2-stage     2-stage       Voltage (V)     220-240     220-240     220-240       IP protection class     X4     X4     X4       Rated power (W)     1000     1000     1000       Max. airflow (m³/h - I/min.)     150/2500     150/2500     150/2500       Sound pressure level (dB(A))     74     74     74       Cable length (m)     7/orange     7/orange     7/orange       Tank capacity (I)     35     35     35       Length x withh x height (cm)     47x45x80     47x45x80     47x45x80	Ref. no.			50000110	5000	0112	50000113
Easy-to-carry handle••Easy-to-carry handleLSU135-EULSU135-UKLSU135-UKYacuum motor type2-stage2-stage2-stageVoltage (V)220-240220-240220-240Frequency (Hz)50-6050-6050-60IP protection classX4X4X4Rated power (W)100010001000Max. airflow (m³/h - l/min.)150/2500150/2500150/2500Yacuum (mm H2O)202020202020Sond pressure level (dB(A))7/47474Cable length (m)7/orange7/orange7/orangeTank capacity (I)353535Length x width x height (cm)47x45x8047x45x8047x45x80	PRODUCT FEATURES						
LSU135-EU     LSU135-UK     LSU135P-UK       Vacuum motor type     2-stage     2-stage     2-stage       Voltage (V)     220-240     220-240     220-240       Frequency (Hz)     50-60     50-60     50-60       IP protection class     X4     X4     X4       Rated power (W)     1000     1000     1000       Max. airflow (m³/h - I/min.)     150/2500     150/2500     150/2500       Sound pressure level (dB(A))     74     74     74       Cable length (m)     7/orange     7/orange     7/orange       Tank capacity (I)     35     35     35       Length x width x height (cm)     47x45x80     47x45x80     47x45x80	Tip out recovery tank			•		•	•
Vacuum motor type     2-stage     2-stage     2-stage       Voltage (V)     220-240     220-240     220-240       Frequency (Hz)     50-60     50-60     50-60       IP protection class     X4     X4     X4       Rated power (W)     1000     1000     1000       Max. airflow (m³/h - l/min.)     150/2500     150/2500     150/2500       Vacuum (mm H2O)     2020     2020     2020       Sound pressure level (dB(A))     74     74     74       Cable length (m)     7/orange     7/orange     7/orange       Tank capacity (l)     35     35     35	Easy-to-carry handle			•		•	•
Voltage (V)     220-240     220-240     220-240     220-240       Frequency (Hz)     50-60     50-60     50-60       IP protection class     X4     X4     X4       Rated power (W)     1000     1000     1000       Max. airflow (m³/h - I/min.)     150/2500     150/2500     150/2500       Vacuum (mm H2O)     2020     2020     2020       Sound pressure level (dB(A))     74     74     74       Cable length (m)     7/orange     7/orange     7/orange       Tank capacity (I)     35     35     35       Length x widh x height (cm)     47x45x80     47x45x80     47x45x80	Technical spe	Technical specifications			LSU1	35-UK	LSU135P-UK
Frequency (Hz)   50-60   50-60   50-60     IP protection class   X4   X4   X4     Rated power (W)   1000   1000   1000     Max. airflow (m³/h - I/min.)   150/2500   150/2500   150/2500     Vacuum (mm H2O)   2020   2020   2020     Sound pressure level (dB(A))   74   74   74     Cable length (m)   7/orange   7/orange   7/orange     Tank capacity (I)   35   35   35     Length x width x height (cm)   47x45x80   47x45x80   47x45x80	Vacuum moto	r type		2-stage	2-st	age	2-stage
IP protection class   X4   X4   X4     Rated power (W)   1000   1000   1000     Max. airflow (m³/h - l/min.)   150/2500   150/2500   150/2500     Vacuum (mm H2O)   2020   2020   2020     Sound pressure level (dB(A))   74   74   74     Cable length (m)   7/orange   7/orange   7/orange     Tank capacity (I)   35   35   35     Length x width x height (cm)   47x45x80   47x45x80   47x45x80	Voltage (V)			220-240	220	-240	220-240
Rated power (W)   1000   1000   1000     Max. airflow (m³/h - I/min.)   150/2500   150/2500   150/2500     Vacuum (mm H2O)   2020   2020   2020     Sound pressure level (dB(A))   74   74   74     Cable length (m)   7/orange   7/orange   7/orange     Tank capacity (I)   35   35   35     Length x width x height (cm)   47x45x80   47x45x80   47x45x80	Frequency (H	z)		50-60	50	-60	50-60
Max. airflow (m³/h - l/min.)   150/2500   150/2500   150/2500     Vacuum (mm H2O)   2020   2020   2020     Sound pressure level (dB(A))   74   74   74     Cable length (m)   7/orange   7/orange   7/orange     Tank capacity (l)   35   35   35     Length x width x height (cm)   47x45x80   47x45x80   47x45x80	IP protection	class		X4	Х	4	X4
Vacuum (mm H2O) 2020 2020   Sound pressure level (dB(A)) 74 74   Cable length (m) 7/orange 7/orange   Tank capacity (l) 35 35   Length x width x height (cm) 47x45x80 47x45x80	Rated power	(W)		1000	10	00	1000
Sound pressure level (dB(A))7474Cable length (m)7/orange7/orangeTank capacity (l)3535Length x width x height (cm)47x45x8047x45x80	Max. airflow (	Max. airflow (m³/h - I/min.)			150/	2500	150/2500
Cable length (m)     7/orange     7/orange     7/orange       Tank capacity (l)     35     35     35       Length x width x height (cm)     47x45x80     47x45x80     47x45x80	Vacuum (mm H2O)			2020	20	20	2020
Tank capacity (I) 35 35   Length x width x height (cm) 47x45x80 47x45x80	Sound pressure level (dB(A))			74	7	4	74
Length x width x height (cm)     47x45x80     47x45x80     47x45x80	Cable length	Cable length (m)			7/ora	ange	7/orange
	Tank capacity	Tank capacity (I)		35 35		5	35
Weight (kg)     13     13     13	Length x widtl	Length x width x height (cm)			47x4	5x80	47x45x80
	Weight (kg)			13	1	3	13

ullet Standard equipment,  $^{\bigcirc}$  Supplementary accessories,  $^{\square}$  Mountable equipment

	Accessories	Ref. no.	Min. required	LSU135-EU	LSU135-UK	LSU135P-UK
Filter						
8	35L ABSORBING DUST FILTER	VA80706	1	•	•	•
$\bigcirc$	FILTER WET LSU135	VA81341	1	0	0	0
Round Brush Nozzle						



	Accessories	Ref. no.	Min. required	LSU135-EU	LSU135-UK	LSU135P-UK
•	DUSTING Ø 38 MM	VA20803	1	•	•	•
Squeegee, Bl	ade, Skirt and Splash Guard					
	BLADE STRIP 38MM	VA86700	1	0	0	0
Vac Nozzle W	Vet					
×	PICK-UP TOOL	VA80853	1	•	•	•
Tube						
$\bigcirc$	SUCTION TUBE ASSEMBLY	VA80401	1	•	•	•
7	WAND ASSEMBLY	VA80711	1	٠	•	•
Crevice Nozz	le					
	CREVICE TOOL Ø 38 MM	VA20806	1	•	•	•
Nozzle						
×	DRY PICK-UP TOOL	VA80036	1	•	•	•
Other						
	BRUSH STRIP KIT 38MM	VA81119	0	0	0	0
Viper Accessory						
<b>*</b>	HOSE APDATOR KIT LSU	VA80654	1	0	o	o
Bag						



Accessories		Ref. no.	Min. required	LSU135-EU	LSU135-UK	LSU135P-UK
<b>D</b>	DUST BAG MICROFIBER 30L PACK 10PCS	VA82058-P10	1	0	0	0

